



Model Number

NBB5-18GM60-I3

Features

- Inductive analog
- Output 0 mA ... 20 mA
- Flush mounting

Accessories

BF 18

Mounting flange, 18 mm

Technical Data

General specifications

Output type	Analog current output
Installation	flush
Output polarity	DC
Measurement range	1 ... 5 mm
Output type	3-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC typ. 20 V DC
Reverse polarity protection		yes
Repeat accuracy		0 ... 80 μ m
No-load supply current	I_0	≤ 12 mA

Analog output

Output type	0 ... 20 mA
Slope of output characteristic	5 mA / mm
Linearity error	$\leq \pm 5$ % of full-scale value
Load resistor	$\leq 1000 \Omega$ typ. 500 Ω
Rate of current rise	
0 ... 20 mA	max. 38.9 A/s
20 ... 0 mA	max. 13.9 A/s
Recovery time	1 ... 10 ms, typ. 5 ms
Adjustment tolerance zero point	$\leq \pm 5$ % of full-scale value
Temperature drift	$\leq \pm 0.15$ %/K of full-scale value
Residual ripple	$\pm 125 \mu$ A

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Connection type	cable PVC, 2 m
Core cross-section	0.5 mm ²
Housing material	brass, nickel-plated
Sensing face	PBT
Degree of protection	IP67


Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007 EN 60947-5-7:2003 IEC 60947-5-7:2003


Approvals and certificates

UL approval	cULus Listed, Class 2 Power Source
CCC approval	CCC approval / marking not required for products rated ≤ 36 V

Dimensions




Electrical Connection



Characteristic Curves

Output characteristics



Reduction factor

