



Model Number

NCB10-30GM40-N0-15M-OG

Features

- 10 mm flush
- Shielded PUR cable for oil and gas sector

Accessories

BF 30
Mounting flange, 30 mm

Technical Data

General specifications

Switching function	Normally closed (NC)
Output type	NAMUR
Rated operating distance	s_n 10 mm
Installation	flush
Assured operating distance	s_a 0 ... 8.1 mm
Actual operating distance	s_r 9 ... 11 mm typ.
Reduction factor r_{AI}	0.32
Reduction factor r_{CU}	0.32
Reduction factor r_{304}	0.72
Output type	3-wire

Nominal ratings

Nominal voltage	U_o 8 V
Switching frequency	f 0 ... 650 Hz
Hysteresis	H 1 ... 10 typ. 5 %
Reverse polarity protection	reverse polarity protected
Short-circuit protection	yes
Suitable for 2:1 technology	yes, Reverse polarity protection diode not required
Current consumption	
Measuring plate not detected	≥ 3 mA
Measuring plate detected	≤ 1 mA
Switching state indicator	LED, yellow

Functional safety related parameters

MTTF _d	1870 a
Mission Time (T_M)	20 a
Diagnostic Coverage (DC)	0 %

Ambient conditions

Ambient temperature	-25 ... 80 °C (-13 ... 176 °F)
Storage temperature	-40 ... 80 °C (-40 ... 176 °F)

Mechanical specifications

Connection type	cable PUR (halogen-free), 15 m, screened, Oil resistant, Flame-retardant as per IEC 60332-1
Core cross-section	2x 0.5 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Degree of protection	IP66 / IP67
Cable	
Bending radius	> 7.5 x cable diameter
Note	The shield is not connected to the sensor.

General information

Use in the hazardous area	see instruction manuals
---------------------------	-------------------------


Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates


UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤ 36 V

Dimensions





Electrical Connection



Data for application in connection with hazardous areas

Equipment protection level	Ga , Gb , Gc (ic) , Da , Mb
----------------------------	-----------------------------

Equipment protection level Ga

Type of protection	intrinsic safety
CE marking	CE 0102

Certificates

Appropriate type	NCB10-30GM...-N0...
ATEX certificate	PTB 00 ATEX 2048 X
ATEX marking	Ⓔ II 1G Ex ia IIC T6...T1 Ga
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012
IECEx certificate	IECEx PTB 11.0037X
IECEx marking	Ex ia IIC T6 Ga
Standards	IEC 60079-0:2004 , IEC 60079-11:2006 , IEC 60079-26:2008

Effective internal capacitance	C_i	$\leq 105 \text{ nF}$ A cable length of 10 m is considered.
--------------------------------	-------	--

Effective internal inductance	L_i	$\leq 100 \text{ }\mu\text{H}$ A cable length of 10 m is considered.
-------------------------------	-------	---

Maximum permissible ambient temperature T_{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values.
---	--

for ATEX

at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 34 \text{ mW}$,
 T6 : 59 °C (138.2 °F)
 T5 : 71 °C (159.8 °F)
 T4 : 99 °C (210.2 °F)
 T3 : 99 °C (210.2 °F)
 T2 : 99 °C (210.2 °F)
 T1 : 99 °C (210.2 °F)
 at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 64 \text{ mW}$,
 T6 : 56 °C (132.8 °F)
 T5 : 68 °C (154.4 °F)
 T4 : 96 °C (204.8 °F)
 T3 : 96 °C (204.8 °F)
 T2 : 96 °C (204.8 °F)
 T1 : 96 °C (204.8 °F)
 at $U_i = 16 \text{ V}$, $I_i = 52 \text{ mA}$, $P_i = 169 \text{ mW}$,
 T6 : 45 °C (113 °F)
 T5 : 57 °C (134.6 °F)
 T4 : 81 °C (177.8 °F)
 T3 : 81 °C (177.8 °F)
 T2 : 81 °C (177.8 °F)
 T1 : 81 °C (177.8 °F)
 at $U_i = 16 \text{ V}$, $I_i = 76 \text{ mA}$, $P_i = 242 \text{ mW}$,
 T6 : 37 °C (98.6 °F)
 T5 : 49 °C (120.2 °F)
 T4 : 63 °C (145.4 °F)
 T3 : 63 °C (145.4 °F)
 T2 : 63 °C (145.4 °F)
 T1 : 63 °C (145.4 °F)

for IECEx

at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 34 \text{ mW}$,
 T6 : 59 °C (138.2 °F)
 T5 : 71 °C (159.8 °F)
 T4 : 99 °C (210.2 °F)
 T3 : 99 °C (210.2 °F)
 T2 : 99 °C (210.2 °F)
 T1 : 99 °C (210.2 °F)
 at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 64 \text{ mW}$,
 T6 : 56 °C (132.8 °F)
 T5 : 68 °C (154.4 °F)
 T4 : 96 °C (204.8 °F)
 T3 : 96 °C (204.8 °F)
 T2 : 96 °C (204.8 °F)
 T1 : 96 °C (204.8 °F)
 at $U_i = 16 \text{ V}$, $I_i = 52 \text{ mA}$, $P_i = 169 \text{ mW}$,
 T6 : 45 °C (113 °F)
 T5 : 57 °C (134.6 °F)
 T4 : 81 °C (177.8 °F)
 T3 : 81 °C (177.8 °F)
 T2 : 81 °C (177.8 °F)
 T1 : 81 °C (177.8 °F)
 at $U_i = 16 \text{ V}$, $I_i = 76 \text{ mA}$, $P_i = 242 \text{ mW}$,
 T6 : 37 °C (98.6 °F)
 T5 : 49 °C (120.2 °F)
 T4 : 63 °C (145.4 °F)
 T3 : 63 °C (145.4 °F)
 T2 : 63 °C (145.4 °F)
 T1 : 63 °C (145.4 °F)

Equipment protection level Gb

Type of protection	intrinsic safety	
CE marking	CE 0102	
Certificates		
Appropriate type	NCB10-30GM...-N0...	
ATEX certificate	PTB 00 ATEX 2048 X	
ATEX marking	Ex II 1G Ex ia IIC T6...T1 Ga	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
IECEx certificate	IECEx PTB 11.0037X	
IECEx marking	Ex ia IIC T6 Ga	
Standards	IEC 60079-0:2004 , IEC 60079-11:2006	
Effective internal capacitance	C _i	≤ 105 nF A cable length of 10 m is considered.
Effective internal inductance	L _i	≤ 100 μH A cable length of 10 m is considered.
Maximum permissible ambient temperature T _{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at U _i = 16 V , I _i = 25 mA , P _i = 34 mW , T6 : 76 °C (168.8 °F) T5 : 91 °C (195.8 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at U _i = 16 V , I _i = 25 mA , P _i = 64 mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at U _i = 16 V , I _i = 52 mA , P _i = 169 mW , T6 : 62 °C (143.6 °F) T5 : 77 °C (170.6 °F) T4 : 81 °C (177.8 °F) T3 : 81 °C (177.8 °F) T2 : 81 °C (177.8 °F) T1 : 81 °C (177.8 °F) at U _i = 16 V , I _i = 76 mA , P _i = 242 mW , T6 : 54 °C (129.2 °F) T5 : 63 °C (145.4 °F) T4 : 63 °C (145.4 °F) T3 : 63 °C (145.4 °F) T2 : 63 °C (145.4 °F) T1 : 63 °C (145.4 °F)	

Equipment protection level Gc (ic)

Type of protection	intrinsic safety	
CE marking	C E	
Certificates		
ATEX certificate	PF 13 CERT 2895 X	
ATEX marking	II 3G Ex ic IIC T6...T1 Gc	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
Effective internal capacitance	C _i	≤ 105 nF A cable length of 10 m is considered.
Effective internal inductance	L _i	≤ 100 μH A cable length of 10 m is considered.
Maximum permissible ambient temperature T _{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at U _i = 20 V , I _i = 25 mA , P _i = 34 mW , T6 : 55 °C (131 °F) T5 : 55 °C (131 °F) T4 : 55 °C (131 °F) T3 : 55 °C (131 °F) T2 : 55 °C (131 °F) T1 : 55 °C (131 °F) at U _i = 20 V , I _i = 25 mA , P _i = 64 mW , T6 : 55 °C (131 °F) T5 : 55 °C (131 °F) T4 : 55 °C (131 °F) T3 : 55 °C (131 °F) T2 : 55 °C (131 °F) T1 : 55 °C (131 °F) at U _i = 20 V , I _i = 52 mA , P _i = 169 mW , T6 : 52 °C (125.6 °F) T5 : 52 °C (125.6 °F) T4 : 52 °C (125.6 °F) T3 : 52 °C (125.6 °F) T2 : 52 °C (125.6 °F) T1 : 52 °C (125.6 °F) at U _i = 20 V , I _i = 76 mA , P _i = 242 mW , T6 : 44 °C (111.2 °F) T5 : 44 °C (111.2 °F) T4 : 44 °C (111.2 °F) T3 : 44 °C (111.2 °F) T2 : 44 °C (111.2 °F) T1 : 44 °C (111.2 °F)	

Release date: 2019-05-13 16:05 Date of issue: 2019-05-13 232395_eng.xml

Equipment protection level Da

Type of protection	intrinsic safety
CE marking	CE 0102

Certificates

Appropriate type	NCB10-30GM...-N0...
ATEX certificate	PTB 00 ATEX 2048 X
ATEX marking	Ex II 1D Ex ia IIIC T135°C Da
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012

Effective internal capacitance	C_i	$\leq 105 \text{ nF}$ A cable length of 10 m is considered.
--------------------------------	-------	--

Effective internal inductance	L_i	$\leq 100 \mu\text{H}$ A cable length of 10 m is considered.
-------------------------------	-------	---

Maximum permissible ambient temperature T_{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 34 \text{ mW}$: 100 °C (212 °F) at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 64 \text{ mW}$: 100 °C (212 °F) at $U_i = 16 \text{ V}$, $I_i = 52 \text{ mA}$, $P_i = 169 \text{ mW}$: 81 °C (177.8 °F) at $U_i = 16 \text{ V}$, $I_i = 76 \text{ mA}$, $P_i = 242 \text{ mW}$: 63 °C (145.4 °F)	
--	--	--

Equipment protection level Mb

Type of protection	intrinsic safety
--------------------	------------------

Certificates

Appropriate type	NCB10-30GM...-N0...
IECEx certificate	IECEx PTB 11.0037X
IECEx marking	Ex ia I
Standards	IEC 60079-0:2004 , IEC 60079-11:2006

Effective internal capacitance	C_i	$\leq 105 \text{ nF}$ A cable length of 10 m is considered.
--------------------------------	-------	--

Effective internal inductance	L_i	$\leq 100 \mu\text{H}$ A cable length of 10 m is considered.
-------------------------------	-------	---

Maximum permissible ambient temperature T_{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 34 \text{ mW}$: 100 °C (212 °F) at $U_i = 16 \text{ V}$, $I_i = 25 \text{ mA}$, $P_i = 64 \text{ mW}$: 100 °C (212 °F) at $U_i = 16 \text{ V}$, $I_i = 52 \text{ mA}$, $P_i = 169 \text{ mW}$: 81 °C (177.8 °F) at $U_i = 16 \text{ V}$, $I_i = 76 \text{ mA}$, $P_i = 242 \text{ mW}$: 63 °C (145.4 °F)	
--	--	--