



Model Number

IA6-12GM35-U-V1

Features

- Inductive analog
- Analog output
0 V ... 5 V

Accessories

BF 12

Mounting flange, 12 mm

V1-W

Female connector, M12, 4-pin, field attachable

V1-G-2M-PUR

Female cordset, M12, 4-pin, PUR cable

V1-W-2M-PUR

Female cordset, M12, 4-pin, PUR cable

Technical Data

General specifications

Output type	Analog voltage output
Installation	quasi flush
Output polarity	DC
Actuating element	mild steel, e. g. 1.0037, SR235JR (formerly St37-2) 18 mm x 18 mm x 1 mm
Measurement range	0 ... 6 mm
Output type	4-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Limit frequency (3dB)		1000 Hz at s = 3 mm
Reverse polarity protection		yes
Short-circuit protection		yes
Repeat accuracy		0 ... 1 μ m
No-load supply current	I_0	≤ 10 mA

Analog output

Output type	0 ... 5 V
Load resistor	$\geq 500 \Omega$
Recovery time	1 ... 10 ms, typ. 5 ms
Adjustment tolerance zero point	$\leq \pm 10$ % of full-scale value
Temperature drift	± 5 % (0 ... 70 °C) ± 10 % (-25 ... 0 °C)
Residual ripple	20 %

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Connection type	Connector plug M12 x 1, 4-pin
Housing material	chromium plated brass
Sensing face	PBT
Degree of protection	IP67


Compliance with standards and directives

Standard conformity	EN 60947-5-2:2007 IEC 60947-5-2:2007 EN 60947-5-7:2003 IEC 60947-5-7:2003
---------------------	--


Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤ 36 V


Dimensions



Electrical Connection



Pinout



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Characteristic Curves

Output characteristics

