Ø16 Emergency Switches

уре	Appearance	Model	Contact block	LED block				
0		S16ER-E1RB	B contact	DC voltage				
D30 (short head)		S16ER-E1R2B	2	— —				
		%The control unit , contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters)						
		Dimensions						
		(unit: mm)						
			Panel thickness: Max. 3.5mm					
	S16ER-E1R							
				<u>R0.6</u>				
			19.6					
		I → I → I → I → I → I → I → I → I → I →						
			Contact block	LED block				
		e	Appearance	Model	B contact	DC voltage		
D30 (short head/ illuminated)	S16ER-E3R	S16ER-E3RB5		1 (5VDC)				
		S16ER-E3R B12	1	1 (12VDC)				
		S16ER-E3R B24		1 (24VDC)				
		S16ER-E3R 2B5		1 (5VDC)				
		S16ER-E3R 2B12	2	1 (12VDC)				
		S16ER-E3R 2B24		1 (24VDC)				
		 The control unit , contact blocks, LED blocks are sold separately. (control unit: bold letters, contact and LED block: regular letters) The LED color is the same as the control unit. 						
		Dimensions		(
			Panel thickness: Max. 3.5mm	unit: mm)				
	STOER-ESR							
				⁺ m				
				£ 1				
				RO.6				

ead

Ø16 Panel Cut-out Dimensions

Туре			A	В	(unit: mm) Panel Cut-out Dimensions	
	Round (S16PR Series)		20	21		
Push Button Switches	Square (S16PRS Series)		20	21		
	Rectangular (S16PRT Series)		25	21	-	
	Round (S16SR Series)		20	21	Min. A ^{±0.5} Ø16.2	
Selector Switches	Square (S16SRS Series)		20	21		
	Rectangular (S16SRT Series)		25	21		
	Round (S16KR Series)		20	21		
Key Selector Switches	Square (S16KRS Series)		20	21		
	Rectangular (S16KRT Series)		25	21		
Mushroom-head Push Button Switches (S16BR Series)			24	24	-	
Emergency Switches (S16ER Series)			40	40	_	
	Round (L16RR Series)		20	21		
Pilot Lights	Square (L16RRS Series)		20	21		
	Rectangular (L16RRT Series)		25	21		